


VdTÜV-Kennblatt for welding consumables

		1 Manufacturer/Supplier "Multimet" Sp. z o. o. ul. Fabryczna 10 POL 59-170 Przemkow		2 No. of VdTÜV-Kennblatt: 18844.00 14.12.2015	
3 Welding consumable*:		Fülldrahtelektrode			
4 Trade name*:		IMT M700Ni			
7 Type*:		EN ISO 17632-A - T 50 6 1Ni M M 1 H5			
11 Diameter range:		1,2 bis 1,6 mm			
12 Auxiliary materials:		Gase EN ISO 14175 - M21			
13 The validity of this Kennblatt will be certified, respectively, in the latest edition of CD-ROM TÜV-eignungsgeprüfte Schweißzusätze					
15 Materials and postweld heat treatment					
Pos	Wb	Group / Material 1	Text	Group / Material 2	Remarks
	U	Gruppe 1.1			
	S	Gruppe 1.1			
	N	Gruppe 1.1			
	U	Gruppe 1.2			
	S	Gruppe 1.2			
	N	Gruppe 1.2			
	S	Gruppe 1.3 (ReH max. 500 MPa)			
	U	Gruppe 1.3 (ReH max. 500 MPa)			
	S	Gruppe 2.1			
	S	Gruppe 2.2 (ReH max. 500 MPa)			
	U	Gruppe 2.2 (ReH max. 500 MPa)			
	S	Gruppe 3.1 (ReH max. 500 MPa)			
	U	Gruppe 3.1 (ReH max. 500 MPa)			
16 Material groups acc. to CR ISO 15608					
21 Root weldability:		verified			
23 Wall thickness:		unbegrenzt			
24 Type of current and polarity:		G+			
25 Welding position according to DIN ISO 6947:		PA, PB, PC, PF			
26 Highest operating temperature in the short-term range as for parent metal, but not higher than:		350 °C			
27 Highest operating temperature in the long-term range max.:		- - - °C			
28 Lowest operating temperature/as for parent metal, but not lower than:		-60 °C			
29 Design stress value/as for parent metal:		wie Grundwerkstoff			
30 For use in the long-term range:		- - -			
31 Resistance to intergranular corrosion proven in accordance with:		- - -			
32 Remarks: S: 580 °C / 3 h N: 920 °C / 0,5 h					
33 The approval test was done on the basis of VdTÜV-Merkblatt 1153. Where nothing different is said under the heading -Remarks-, this welding consumable is suitable provided Annex I Point 4 of the Pressure Equipment Directive 97/23/EC is observed.					
34 Explanations		A tempered L solution annealed and quenched N normalized	S stress-relieved St stabilized U non-annealed V hardened and tempered	W soft annealed	G+ direct current plus pole G- direct current minus pole W alternating current
35 Compiled in accordance with the data of:		TÜV SÜD Industrie Service GmbH, München			
The duplication, circulation, copy and complete edition by photomechanical or similar techniques remain subject to the editor's approval even if only used in extracts. Editor: Verband der TÜV e. V. Distribution: TÜV-Media GmbH, Am Grauen Stein, 51105 Köln - Unternehmensgruppe TÜV Rheinland Group					

*) Statements of the manufacturer

VdTÜV-Kennblatt for welding consumables